



TumbleStone 12x12 (with Bar Tile), Custom Color, Hotel Walkway, Santa Barbara, CA

Product Type:

Paver Tile

Recommended Use:

Exterior, Interior, Residential, Commercial
Pedestrian, Light Vehicular, Floor or Wall Veneer

Installation:

Mortar (aka wet) Set, Thin Set (CTMA method)

Packaging / Weight:

Boxed (13 pcs), Pallets (18 boxes), 8 lbs per sq ft

Suggested Finishes:

Natural. Light, Medium or Heavy Sandblast.

Complementary Paver Tiles:

Tumblestone 8x8

Matching Accessory / Trim Units::

Surface Bullnose 12x12

Color Selection:

Select colors from the current Cal-Ga-Crete or Davis Colors chart.

Test Results:


<u>Test Results:</u>	<u>ASTM #</u>	<u>Results</u>	<u>Comments</u>
Water Absorption	C-373	7.75%	Unsealed
Breaking Strength	C-648	988 lbs	0.75" thickness
Modulus of Rupture	C-674	1374	0.75" thickness
Abrasive Hardness	C-501	27	
Coefficient of Friction (COF)	C-1028-07	0.70	Smooth Surface
Coefficient of Friction (COF)	C-1028-07	0.77	Light Sandblast
Compressive Strength	C-140-75	6027	0.825" thickness

Notes:

Expect naturally occurring color variations typical for concrete, unglazed ceramic and stone tile products. Apply a quality sealer for wear factor improvement and ease of maintenance. Notify the factory in case of intended exterior use in freeze-thaw climates.

Technical and Contact Information:

Review the latest care and installation recommendations available on Cal-Ga-Crete's website www.calgacrete.com. For inquiries email info@calgacrete.com or call 310-639-8960.



Design Style:

Antique Marble
Worn Stone Tile
Tumbled Marble